



10 SEER Air Handler

10 SEER Manejadoras de Aire-Serie

MODEL / MODELO: CTA10C0_A SPECIFICATIONS / ESPECIFICACIONES

Model			CTA10C036A	CTA10C060A
Power supply		V/Ph/Hz	208V~230V/1Ph/60Hz	208V~230V/1Ph/60Hz
Cooling	Capacity	Btu/h	32755	49474
	Capacity	W	9600	14500
	Input	W	3529	5480
	Rated current	A	16.20	25.16
	EER	Btu/h.W	9.28	9.03
	SEER	Btu/h.W	10.30	10.02
Moisture Removal (kg/h)		l/h	3.57	5.73
Max. input consumption		W	4234	6900
Max. current		A	20.77	33.85
Indoor coil	Number of row		2	3
	Fin spacing	mm	1.5	1.5
	Fin material		Hydrophilic Aluminium Fin	Hydrophilic Aluminium Fin
	Tube outside diameter	mm	Φ7	Φ7
	Tube material		Inner Screw	Inner Screw
	Coil length x height x width	mm	336X26.74X413 (X2)	378X40X443 (X2)
	Number of circuit		4	6
Indoor fan motor	Model		YDK130-6X	YDK250-6X-2
	Brand		kangbao	Weiling
	Input	W	240	480
	Output	W	130	250
	Capacitor	μF	6	12
	Speed (Hi/Me/Lo)	rpm	910/780	800/730
Indoor air flow		m3/h	1700	2500
Indoor noise level		dB(A)	51-56	51~57
Indoor dimension	Unit (WxHxD)	mm	460×774×520	500×970×550
	Packing (WxHxD)	mm	520×834×565	560×1030×595
Indoor weight	Net	kg	37	45
	Gross	kg	39	48
Throttle type			Piston	Piston
Operation temperature range		°C	16-32	16-32